

# SOLRAD-9

# REDUCED SOLAR X-RAY FLUXES

### 68-017A-01E

This data set has been restored. The DR and DS tape are 9 track and EBCDIC. The DR tape is a 3480 cartridge and the DS tape is 6250 BPI. The DR and DS numbers along with the time spans are given as follows:

DR #	DS #	DD #	FILES	TIME SPAN
DR02923	DS02923	D-29064 D-29065 D-29066	3	03/14/68 - 06/30/68 07/01/68 - 09/30/68 10/01/68 - 12/31/68
DR02924	DS02924	D-29067 D-29068 D-29069	3	01/01/69 - 03/31/69 04/01/69 - 06/30/69 07/01/69 - 09/30/69
DR02925	DS02925	D-29070 D-29071 D-29072	3	10/01/69 - 12/31/69 01/01/70 - 03/31/70 04/01/70 - 06/30/70
DR02926	DS02926	D-29073 D-29074 D-29075	3	07/01/70 - 09/30/70 10/01/70 - 12/31/70 01/01/71 - 03/31/71
DR02927	DS02927	D-29076 D-29077 D-29078	3	04/01/71 - 06/30/71 07/01/71 - 09/30/71 10/01/71 - 12/31/71
DR02928	DS02928	D-29079 D-29080 D-29081	3	01/01/72 - 03/31/72 04/01/72 - 06/21/72 07/01/72 - 09/30/72

# SOLRAD-9

# REDUCED SOLAR X-RAY FLUXES

# 68-017A-01E

This data set catalog consists of Solrad-9 data tapes. The tapes are 556 BPI, BCD, 7 track, with 1 file and were created on a CDC 3800 computer.

<u>D#</u>	<u>C#</u>	TIME SPAN
D-29064	C-18735	3/14/68 - 6/30/68
D-29065	C-18736	7/01/68 - 9/30/68
D-29066	C-18737	10/01/68 - 12/31/68
D-29067	C-18738	1/01/69 - 3/31/69
D-29068	C-18739	4/01/69 - 0/30/69
D-29069	C-18740	7/01/69 - 9/30/69
D-29070	C-18741	10/01/69 - 12/31/69
D-29071	C-18742	1/01/70 - 3/31/70
D-29072	C-18743	4/01/70 - 6/30/70
D-29073	C-18744	7/01/70 - 9/30/70
D-29074	C-18745	10/01/70 - 12/31/70
D-29075	C-18746	1/01/71 - 3/31/71
D- 29076	C-18747	4/01/71 - 0/30/71
0-29077	C-18748	7/01/71 - 9/35/71
5-29078	C-18749	10/01/71 - 12/31/71
29079	C-18750	1/01/72 - 5, 31/72
- 1-29 <b>0</b> 80	C-18751	4/01/72 - 6/11/72
D- 29031	C-18752	7/01/72 - 9/3//72

DICOS 6/61/17

#### DESCRIPTION OF SOLRAD 9 FLUX DATA TAPE

Solar radiation measurements collected by the memory system on SOLRAD 9 were processed on a CDC-3800 computer at the Naval Research Laboratory. The reduced flux data from the various experiments are stored on standard 7-track magnetic tapes as strings of 6-bit BCD characters written in odd parity. These tapes usually contain one or more calendar months of reduced data and are unlabeled, i.e., the flux data begins in the first record. The date and time (UT) associated with each data sample are uniquely defined by appropriate fields within the format. The following paragraphs describe the layout of the data on a tape as well as the format into which the measurements have been encoded.

The overall organization of the data on a SOLRAD 9 flux data tape is shown in Figure 1. The data are partitioned into records and files according to the following scheme. Each record contains one hour of data. Each file contains one calendar day of data and is thus composed of a maximum of 24 records. The records are of variable length, since the number of minutes of data present in each hour commonly varies. The files are also of variable length since occasionally there are days during which one or more hours of data are lacking.

The satellite collected samples of data once a minute. Each minute of reduced data was encoded into a string of 80 BCD characters suitable for punching on cards. (Since the word length on the CDC-3800 is 48 bits, each word could contain 8 such BCD characters; hence, each minute of reduced data was contained in 10 computer words). The maximum length of any record is then 60 (minutes/hour) x 80 (characters/minute) = 4800 characters (or 600 CDC-3800 computer words). The several 80-character strings for an hour are simply concatenated within a record, the record ending when the data for that hour ends. The length of any record is thus an integer multiple of 80 characters (or 10 words), this multiple being the number of minutes of data available for that hour.

The format of the 80-character string into which each minute of data is encoded is shown in Figure 2 along with an example of a FORTRAN Format statement that can be used to decode it. The following are general comments about the format and the measurements it contains:

- (1) In each string, the date is specified by giving the last digit of the year followed by the day of the year, and the time (UT) is given in hours and minutes. The actual time at which any one measurement was collected by the satellite is usually within  $\pm$  30 seconds of the recorded time, since the recorded time has been rounded to the nearest minute.
- (2) The measurements obtained from experiments 5, 6, and 7B, are given in units of energy flux, ergs/cm²/sec, and are encoded into a modified floating-point form which consists of a 2-digit decimal fraction followed by a one-digit signed decimal exponent. This same floating-point form is used for "background" values recorded in the field labeled "EX7Q", but the units are counts. These background data were obtained from experiment 7 when its detector was pointed in the opposite direction from the sun, and are used as an indicator of the possible presence of charged particle interference in the other measurements.
- (3) A zero value in any one of the floating-point fields indicates the absence of a measurement from that experiment for that minute. This will occur most often because of the presence of charged particle interference which rendered that measurement meaningless.

(4) Periods of time lasting several minutes during which no solar radiation measurements could be obtained, such as when the satellite passed through the earth's shadow or when the memory system was being read-out, will of course be missing from the tape entirely.

A more detailed explanation of each field in the format is given below:

COLUMN(s)	LABEL	CONTENTS Blank
2-5	YDAY	Date of this group of measurements
		Col. 2 - last digit of the year
		Col. 3 - day of the year.
6		Blank
7-10	HRMN	Universal time for this group of
		measurements.
		Col. 7,8 + hour
		Col. 9,10 - minute
11		Blank
12-13	ST	Station number (usually = M1)
14-15		Blank
25-28	EXP5	Experiment 5, 8-16°A x-ray flux
29		Identifies A or B detector of exp. 5
30		Blank
31-34	EXP6	Experiment 6, 1-80A x-ray flux
35		Identifies A or B detector of exp. 6
36		Blank
37-40	EX7Q	Experiment 7 Quiescent (Background)
		counts
41		Blank
42-45	EX7B	Experiment 7B, 0.5-30A x-ray flux
46-52		Blank
53-56	IPWA	Solar aspect angle used to normalize
		the data (usually =0)
57-79		Blank
80	M	Version of program used to reduce this
		<pre>group of measurements (usually = 1)</pre>

A typical SOLRAD 9 flux data record is shown in Figure 3 where successive blocks of 80 characters have been printed on consecutive lines until the end of the record was encountered. The record shown is the first record from the file for 1 August 1971 which contains 27 minutes of data, from 0000 UT through 0026 UT.

In the table below are listed the 6-bit codes that are used to represent the BCD characters which are written onto these SOLRAD 9 flux data tapes.

BCD CHARACTER	6-BIT OCTAL CODE	!	BCD CHARACTER	6-BIT OCTAL CODE
0	00	1	8	10
1	01	1	9	11
2	02	<u>!</u>	+	20
3	03	1	A	21
4	04	1	В	22
5	05	!	-	40
6	06	1	M	44
7	07	į	Blank	60

• • •		CHARACTER POSITIONS	
FILE	RECORD	123456789101180	DESCRIPTION
1	1	1213 0000 1	
			on 1 Aug 1971
		1 2 1 3 0 0 2 6 1	
(	2	1213 0101 1	Data for the second hour on 1 Aug 1971
		1213 0159 1	σ, πως
		4	7
1:	24	1213 2300 1	Data for the last hour
			on 1 Aug 1971
		1213 2359 1	
1	25	(END OF FILE)	End of File 1
2	11.	1214 0000 1	Data for the first hour
			on 2 Aug 1971
		1214 0059 1	
2	2	1214 0134 1	Dada for the second hour
		1214 0159 1	on 2 Aug 1971
		1214 0159 1	
2	24	1214 2300 1	Data for the last hour
			on 2 Aug 1971
		1214 2353 1	
2	<i>સ</i> ક	(END OF PILE)	End of File 2
		4	
3/		1243 00 x x 1	Data for the first hour
			on 31 Aug 1971
•		1243 00 XX 1	
3/	24	1243 23 x x 1	
		1243 23 X X /	on 31 Aug 1971
31	25	(END OF FILE)	End of File 31
32	α3 /	(END OF FILE)	End of Tape
	Fig. 1	- DIAGRAM of SOLRAD 9 X-ray A	-lux Data Tape
	J		

```
COLS 1 2 3 4 5 //7 R
123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345679901234567990123456799012345
```

Figure 2. Format for One Minute of SOLRAD 9 Flux Data

2 2 5 5 5 E 6 2 2 S ks 2 2 9 DATA SPLPAN 11+110 11-6 11=6 3+(34) 11-0 11+114 5+n CN+N 51 + T2 ;3 ニキスシ 242 45-0 2+25 57+0 611+1 13+04 F. (A + C.) 2+2 シャンシ 2+2 2+23 2+23 (1+1) 7+2 1-0+05 14+0 1440 17+13 E+ / 13+6 3+6 3+1 N+0 51+05 -+ 70 -1+4 5 ↑ ₹ 2 + 7 7+ 14+2 17+6 5 7 14+0 2+24 14+6 14+0 1 HAS 2160 CHAPACTERS OF 26-515 おやすの形 35-55 52-56 35-54 52=55 52-54 52=51. 14-41 17-54 76-58 **カジー** かた 15-96 35-55 40-54 44-51 44-64 52-51 10+0H 3 = V P 3-30 35-56 13-ZH 87-57 9V-61 79-4B 79-1H 70-48 70-AU 8V-01 40-66 82-48 77-1H AV-01 82-4B 79-4B 79-4H HV-01 77-44 JU-UE 8V-6/ 11V-07 9-18 #5+43 コンニクエ 77-48 1-31 PECU Σ Σ Ξ Z Z Σ I Σ Σ Σ 2000 0000 00100 200 2015 0 0 0 1/3 2 2 2 3 3 5000 7000 2225 NANZ 2222 BP 12 0013 2014 61517 **BO18** 500 B のなる 2 2 2 3 252 5223 FILE 213 213 213 213 213 213 213 213 2.5 213 213 213 213 213 213 213 213 213 213 213 213 253

Figure 3. One record of SOLRAD 9 Flux Data

*E NO PROCEDURE	
·	
* F X F I S C I S	
<u>п</u> U	
TAPE NO. 1	
FILE NO.	
PECORD 2 8/74-80156-417-513+06+98074-80253-417-512+000359-485-512+011-68074980453-434-513+000+9807 4:89553-426-512+011-6	
***** JOB DONE. *EXE TFLIST BS	to De Ci
INPUT PARAMETERS ARE: ED SR=18222=2 1 1 3	
	60 N
	61 5 61
FILE NO.	(a)
RECORD 18223 LENGTH 124 8565235617-313-413-411-68366235717-315-413+411-68366235817-313-413+00(+08366235917-312-416+010+0	69
***** JOB DONE.	(1 12
WEG LPS	e e e
2//4/68	
DR 02/23	
7 2	• "
	7 9
dCN <del>S</del>	1

GON \$

- 1
B0J 19:06:42
SEXEC LIST BS
INPUT PARAMETERS ARE: BC FL=3=3
TAPE NO. 1
RECORD 1 LENGTH 120
2/83/04/04/04/04/04/04/04/04/08/04/08/7-614+000+02183000674-435-514+000+02183000787-452-513+011-6218 3000885-452-515+000+0
TAPE NO. 1 FILE NO. 1
RECORD 2 2183000985-661-514+000+02183001082-6270-514+000+0218300183001282-666-5134011-6218
3001385-461-514+000+0
TAPE NO. 1 FILE NO. 1
RECORD 3 LENGTH 120
2183001485-426-514+000+02183001582-452-514+000+02183001685-461-514+000+02183001785-461-513+000+0218 3001890-435-514+000+0
TABE NO 1 ETIE NO 1
RECORD 15033 LENGTH 120
2274232169-444-514+000+02274232267-444-514+000+02274232369-487-614+000+02274232464-435-514+000+0227
0+000+010-02+-10020
TAPE NO. 1 BECORD 15034 LENGTH 120
274232667-417-517+000+02274232764
4233067-417-517+000+0
TAPE NO. 1 FILE NO. 1
RECORP 1593> 2 <mark>274238</mark> 167-444-518+000+02274233264-426-521+000+02274233326-587-622+000+0
**** JOB DONE. \$NOTE E0_ 19:11:13
0
1/30/12
0-29081
THE PARTY OF THE P